

Package: zoeppritz (via r-universe)

September 16, 2026

Type Package

Title Seismic Reflection and Scattering Coefficients

Version 1.0-9

Date 2023-08-19

Author Jonathan M. Lees [aut, cre]

Maintainer Jonathan M. Lees <jonathan.lees@unc.edu>

Description Calculate and plot scattering matrix coefficients for plane waves at interface.

License GPL (>= 2)

NeedsCompilation no

Repository <https://jonathanlees.r-universe.dev>

Date/Publication 2023-08-19 17:30:47 UTC

RemoteUrl <https://github.com/cran/zoeppritz>

RemoteRef HEAD

RemoteSha bf91f8b6b6a60783b1b9d715f4432cdd74a0c614

Contents

zoeppritz-package	2
piczoeppritz	3
plotzoeppritz	4
pzoeppritz	5
zoeppritz	7
Index	10

zoeppritz-package

Zoeppritz Equations

Description

Calculate and plot scattering matrix coefficients for plane waves at interface.

Author(s)

Jonathan M. Lees<jonathan.lees@unc.edu> Maintainer: Jonathan M. Lees<jonathan.lees@unc.edu>

References

Young,~G.B., Braile, L. W. 1976. A computer program for the application of Zoeppritz's amplitude equations and Knott's energy equations, *Bulletin of the Seismological Society of America*, vol.66, no.6,1881-1885.

K. Aki and P.G. Richards.*Quantitative seismology*. University Science Books, Sausalito, Calif., 2nd edition, 2002.

Examples

```
##### demo(ZOEP)

##### Incident wave in Low velocity layer
alpha1 = 4.98
  beta1 = 2.9
    rho1 = 2.667

alpha2 = 8.0
  beta2 = 4.6
    rho2 = 3.38

App = pzoeppritz( "Amplitude" , alpha1, alpha2, beta1, beta2, rho1 ,rho2, "P", "ALL");
App = pzoeppritz( "Amplitude" , alpha1, alpha2, beta1, beta2, rho1 ,rho2, "S", "ALL");
App = pzoeppritz( "Energy" , alpha1, alpha2, beta1, beta2, rho1 ,rho2, "P", "ALL");
App = pzoeppritz( "Potential" , alpha1, alpha2, beta1, beta2, rho1 ,rho2, "P", "ALL");

##### Incident wave in high velocity layer
alpha1 = 8.0
  beta1 = 4.6
    rho1 = 3.38

alpha2 = 4.98
```

```

beta2 = 2.9
rho2 = 2.667

App = pzoeppritz( "Amplitude" , alpha1, alpha2, beta1, beta2, rho1 ,rho2, "P", "ALL");

App = pzoeppritz( "Amplitude" , alpha1, alpha2, beta1, beta2, rho1 ,rho2, "S", "ALL");

```

piczoeppritz

Show Scattering Diagram Cartoon

Description

Adds a small diagram showing two layers and labeled scattered ray paths.

Usage

```
piczoeppritz(LL = list(x = c(0, 1), y = c(0, 1)), chincw = "P")
```

Arguments

LL	Bounds of Box for plotting
chincw	character for incident wave

Details

This code simply adds a small cartoon showing incoming and outgoing waves in scattering matrix.

Value

Graphical side effect.

Author(s)

Jonathan M. Lees<jonathan.lees@unc.edu>

See Also

pzoeppritz

Examples

```

plot(c(0,1), c(0,1), type='n')
piczoeppritz(LL = list(x = c(0.5, 0.75), y = c(0.5, 0.75)), chincw = "P")

```

plotzoeppritz

Plot Scattering (Zoeppritz) Coefficients

Description

Plot Scattering (Zoeppritz) Coefficients

Usage

```
plotzoeppritz(A, zoepcols = c("red", "green", "blue", "purple"), zoeppty = c(1, 1, 1, 1))
```

Arguments

A	list output of pzoeppritz or zoeppritz
zoepcols	vector of 4 colors
zoeppty	vector of 4 line types

Details

Used to plot the matrix of scattering coefficients with different colors and/or line types.

Value

Graphical side effects.

Author(s)

Jonathan M. Lees<jonathan.lees@unc.edu>

See Also

zoeppritz, pzoeppritz, piczoeppritz

Examples

```
alpha1 = 4.98
beta1 = 2.9
rho1 = 2.667

alpha2 = 8.0
beta2 = 4.6
rho2 = 3.38
##### create the scattering matrix:
App = pzoeppritz( "Amplitude" , alpha1, alpha2, beta1, beta2, rho1 ,rho2, "P", "NONE");

##### plot
plotzoeppritz(App)
```

pzoeppritz

*Plot Scattering (Zoeppritz) Coefficients***Description**

Calculate and plot the P and S-wave scattering amplitudes for a plane wave at an interface.

Usage

```
pzoeppritz(chtype = "Amplitude", alpha1, alpha2,
  beta1, beta2, rho1, rho2, chincw = "P",
  choutkind = "ALL")
```

Arguments

chtype	character, type of output, one of: Amplitude, Potential, Energy
alpha1	P-wave Velocity of Upper Layer, km/s
alpha2	P-wave Velocity of Lower Layer, km/s
beta1	S-wave Velocity of Upper Layer, km/s
beta2	S-wave Velocity of Lower Layer, km/s
rho1	Density of Upper Layer, kg/m ³
rho2	Density of Lower Layer, kg/m ³
chincw	Incident Wave: P, S
choutkind	character, type of out put one of: P, S, ALL, NONE

Details

Front end for zoeppritz program.

Value

List output of zoeppritz call:

angle	Incident angles, degrees
rmat	Matrix of 4 by n reflection coefficients for each angle
rra	Matrix of 4 by n real part of scattering matrix
rra	Matrix of 4 by n imaginary part of scattering matrix
ang	Matrix of 4 by n phase angle
incw	integer, from input parameter
icoef	integer, from input parameter
alphacrit	critical angle

Note

This front end is easier to call because it is more verbose. Creates a plot of the coefficients versus incident angle. If coefficients are complex, they are replaced with NA and they are thus not plotted.

Author(s)

Jonathan M. Lees<jonathan.lees@unc.edu>

References

Young,~G.B., Braile, L. W. 1976. A computer program for the application of Zoeppritz's amplitude equations and Knott's energy equations, *Bulletin of the Seismological Society of America*, vol.66, no.6,1881-1885.

K. Aki and P. G. Richards. *Quantitative seismology*. University Science Books, Sausalito, Calif., 2nd edition, 2002.

See Also

zoeppritz, pzoeppritz, piczoeppritz

Examples

```
##### Incident wave in Low velocity layer

alpha1 = 4.98
beta1 = 2.9
rho1 = 2.667

alpha2 = 8.0
beta2 = 4.6
rho2 = 3.38

App = pzoeppritz( "Amplitude" , alpha1, alpha2,
beta1, beta2, rho1 ,rho2, "P", "ALL");

App = pzoeppritz( "Amplitude" , alpha1, alpha2,
beta1, beta2, rho1 ,rho2, "S", "ALL");

##### Incident wave in high velocity layer

alpha1 = 8.0
beta1 = 4.6
rho1 = 3.38

alpha2 = 4.98
beta2 = 2.9
rho2 = 2.667

App = pzoeppritz( "Amplitude" , alpha1, alpha2,
beta1, beta2, rho1 ,rho2, "P", "ALL");

App = pzoeppritz( "Amplitude" , alpha1, alpha2,
```

```
beta1, beta2, rho1 ,rho2, "S", "ALL");
```

zoeppritz

Zoeppritz Equations

Description

Calculate the P and S-wave scattering amplitudes for a plane wave at an interface.

Usage

```
zoeppritz(icoef, vp1, vp2, vs1, vs2, rho1, rho2, incw)
```

Arguments

icoef	type of out put Amplitude=1, Potential=2, Energy=3
vp1	P-wave Velocity of Upper Layer, km/s
vp2	P-wave Velocity of Lower Layer, km/s
vs1	S-wave Velocity of Upper Layer, km/s
vs2	S-wave Velocity of Lower Layer, km/s
rho1	Density of Upper Layer, kg/m ³
rho2	Density of Lower Layer, kg/m ³
incw	integer, Incident Wave: P=1, S=2

Details

Coefficients are calculated at angles from 0-90 degrees. Zero is returned where coefficients are imaginary.

Value

List:

angle	Incident angles (degrees)
rmat	Matrix of 4 by n reflection coefficients for each angle
rra	Matrix of 4 by n real part of scattering matrix
rra	Matrix of 4 by n imaginary part of scattering matrix
ang	Matrix of 4 by n phase angle
incw	integer, from input parameter
icoef	integer, from input parameter

Note

Based on the fortran algorithm in Young and Braile. Uses a linear approximation by Aki and Richards.

Author(s)

Jonathan M. Lees<jonathan.lees@unc.edu>

References

Young, G.B., Braile, L. W. 1976. A computer program for the application of Zoeppritz's amplitude equations and Knott's energy equations, *Bulletin of the Seismological Society of America*, vol.66, no.6,1881-1885.

K. Aki and P.G. Richards.*Quantitative seismology*. University Science Books, Sausalito, Calif., 2nd edition, 2002.

See Also

pzoeppritz, plotzoeppritz

Examples

```
##### set up 2-layer model

alpha1 = 4.98
beta1 = 2.9
rho1 = 2.667

alpha2 = 8.0
beta2 = 4.6
rho2 = 3.38
##### P-wave incident = 1
incw=1;
icoef=1

A = zoeppritz(icoef, alpha1, alpha2, beta1, beta2, rho1,rho2, incw)

plot(A$angle, A$rmat[,1], xlab="Incident Angle", ylab="Ratio of Amplitudes",
main="P-wave incident/P-wave Reflected" )

plot(A$angle, A$rmat[,2], xlab="Incident Angle", ylab="Ratio of Amplitudes",
main="P-wave incident/S-wave Reflected" )

plot(A$angle, A$rmat[,3], xlab="Incident Angle", ylab="Ratio of Amplitudes",
main="P-wave incident/P-wave Refracted" )

plot(A$angle, A$rmat[,4], xlab="Incident Angle", ylab="Ratio of Amplitudes",
main="P-wave incident/S-wave Refracted" )
```

```
##### S-wave incident = 2
      incw=2
      icoef=1

A = zoeppritz(icoef, alpha1, alpha2, beta1, beta2, rho1,rho2,  incw)

plot(A$angle, A$rmat[,1], xlab="Incident Angle", ylab="Ratio of Amplitudes",
     main="S-wave incident/P-wave Reflected" )

plot(A$angle, A$rmat[,2], xlab="Incident Angle", ylab="Ratio of Amplitudes",
     main="S-wave incident/S-wave Reflected" )

plot(A$angle, A$rmat[,3], xlab="Incident Angle", ylab="Ratio of Amplitudes",
     main="S-wave incident/P-wave Refracted" )

plot(A$angle, A$rmat[,4], xlab="Incident Angle", ylab="Ratio of Amplitudes",
     main="S-wave incident/S-wave Refracted" )
```

Index

- * **aplot**
 - piczoeppritz, [3](#)
- * **hplot**
 - plotzoeppritz, [4](#)
 - pzeppritz, [5](#)
- * **misc**
 - pzeppritz, [5](#)
 - zoeppritz, [7](#)
- * **package**
 - zoeppritz-package, [2](#)

piczoeppritz, [3](#)
plotzoeppritz, [4](#)
pzeppritz, [5](#)

zoeppritz, [7](#)
zoeppritz-package, [2](#)